

INSTALLATION INSTRUCTIONS

Column.

Preparation before installing:

Wet the pieces by soaking them in water for 2 hours, and then dry them by leaving them to drain for 10 minutes before installation to prevent them from absorbing water from the mortar.

Material to be used:

Piece PED-33 acts as the base and the capital of the Column. The COL-33 pieces that will form the Column.

Piece RBR-12R and the Pillar Cap CK-50 to integrate the column into balustrades.

Recommended products:

- White tile Cement (COLA-SAS): It comes ready for use in our tins, just add water.
- SAS-FUGUE waterproof surface sealant: This priming layer should be applied to achieve extra protection and optimal balustrade aging.
- We recommend type A grey mortar for filling the column.

Installation:

- Place the pedestal PED-33, which acts as the base of the Column, on the foundations, which must be perfectly levelled.
- The column must always be reinforced
- The COL-33 pieces, with male and female parts, are mounted to the required height.
- If the column is to support light weights (on no account are major loads admissible) it will be reinforced with 10/12 mm rods and filled with type A grey mortar. The inside should be painted with a cement grout to make sure that the pieces do not crack due to the contractions.
- To finish the column, the piece PED-33 should be placed as capital.
- To integrate the Column in balustrades the pedestal should be supplemented with the CK-50 Pillar Cap to adapt the height to the plinth to that of the balustrade (Rail RBR-50).
- To fit Rail RBR-50 with the circumference of the column use piece RBR-12R which has a rounded end.

Precautions to be taken into account:

- Make a diagram before starting.
- Do not install in very hot or very cold days.
- To reinforce the Column use 10/12 mm-diameter rods.
- The Column can only support light loads.
- The inside should be painted with grout.
- Wet the column 8 hours after installing it.
- After a week, and once it is dry, paint the unit with our SAS-FUGUE colourless surface waterproof sealant.

